

PKA-AL12NL & PUY-AK12NL
12,000 BTU/H WALL-MOUNTED INDOOR UNIT
12,000 BTU/H COOLING ONLY OUTDOOR UNIT



Job Name:

System Reference:

Date:



INDOOR Unit ... PKA-AL12NL
OUTDOOR Unit ... PUY-AK12NL

INDOOR UNIT FEATURES

- Wi-Fi Optional: A Wireless Interface Adapter can be ordered as an accessory for field installation.
- Swing Mode: An indoor unit with this capability can move air throughout the room like an oscillating fan.
- Light Commercial: Light commercial applications include small offices, restaurants, and retail.
- Horizontal Vane Control: Horizontal Vane Control allows the indoor unit vanes to be moved left and right to provide even temperatures throughout a space.
- Four Speed Fan: Adjust the fan between four speed settings to optimal comfort.
- Auto Changeover: The unit will automatically switch between heating and cooling modes to maintain your desired temperature.
- Auto Vane Control: Auto Vane Control directs outlet vanes to move left, right, up, and down. This airflow control provides even temperatures throughout a space.

OUTDOOR UNIT FEATURES

- Inverter Driven Compressor: Inverter technology uses only the precise amount of energy needed to keep a space comfortable.
- Blue Fin Coating: Anti-corrosion coating that protects the outdoor heat exchanger against salt, sulfur, and other airborne contaminants that impact the efficiency and performance of the outdoor units.
- Seacoast Protection: An anti-corrosion treatment applied to the aluminum fins of the heat exchanger of the outdoor unit to protect against corrosion caused by salt, sulfur, and other airborne contaminants, especially in coastal and industrial areas.
- Low Ambient Cooling: Low ambient cooling down to -40°F providing 100% capacity with front, side and rear wind baffle kit
- Low Ambient Cooling: Low ambient cooling down to 0°F providing 100% capacity with front wind baffle kit

SPECIFICATIONS: PKA-AL12NL & PUY-AK12NL

Cooling at 95F ¹	Maximum Capacity	Btu/h	12200
	Rated Capacity	Btu/h	12000
	Minimum Capacity	Btu/h	4300
	Maximum Power Input	W	830
	Rated Power Input	W	810
	Moisture Removal	Pints/h	3
	Sensible Heat Factor		0.73
Efficiency	Power Factor [208V / 230V]	%	81 / 81
	SEER2		21.10
	EER2 ¹		14.80
Electrical	ENERGY STAR® Certified		Yes
	Voltage, Phase, Frequency	V AC / V AC , Ø , Hz	208 / 230 , 1 , 60
	Guaranteed Voltage Range	V AC	198 - 253
	Voltage: Indoor - Outdoor, S1-S2	V AC	208/230
	Voltage: Indoor - Outdoor, S2-S3	V DC	12-24
	Short-circuit Current Rating [SCCR]	kA	5
	Recommended Fuse/Breaker Size (Outdoor)	A	20
	Recommended Wire Size [Indoor - Outdoor]	AWG	14
Indoor Unit	Breaker Size	A	
	Fan Motor Output	W	30
	Fan Motor Type		DC Motor
	Airflow Rate at Cooling, Dry	CFM	265 , 290 , 325 , 385
	Airflow Rate at Cooling, Wet	CFM	215 , 255 , 320 , 375
	Sound Pressure Level [Cooling]	dB (A)	34 , 37 , 40 , 43
	Dual Barrier Coating on Fan		No
	External Finish Color		0.7PB 9.2/0.4
	Unit Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	35-11/32 x 9-11/32 x 11-25/32 [898 x 237 x 299]
	Package Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	38-1/4 x 13-7/16 x 14-3/16 [970 x 340 x 360]
	Unit Weight	lbs [kg]	28 [12.70]
IDU Operating Temp. Range	Package Weight	lbs [kg]	32 [14.50]
	Cooling Intake Air Temp [Maximum / Minimum]	°FDB , °FWB / °FDB , °FWB	90 , 73 / 66 , 59
Outdoor Unit	MCA	A	16
	MOCP	A	27
	Fan Motor Output	W	51
	Airflow Rate Cooling	CFM	1590
	Coating on Heat Exchanger (Bluefin, Sea Coast)		Yes , Yes
	Sound Pressure Level, Cooling ¹	dB (A)	44
	Compressor Type		Twin Rotary
	Compressor Model		SRB140FQHMC-L1
	Compressor Oil [Type // Charge]	// oz	RM68EH // 16
	External Finish Color		Munsell 3Y 7.8/1.1
	Unit Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	34-19/64 x 11-13/16 x 24-13/16 [871 x 300 x 630]
	Package Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	37-1/16 x 16-3/16 x 32-1/4 [941 x 411 x 819]
	Unit Weight	lbs [kg]	99 [45]
	Package Weight	lbs [kg]	112 [51]
ODU Operating Temp. Range	Cooling Intake Air Temp [Maximum / Minimum*]	°FDB	115 / 23
	Cooling Thermal Lock-out / Re-start Temperatures**	°FDB	N/A / N/A
Refrigerant	Type		R454B
	Pre-Charged Refrigerant Amount	lbs , oz	4 , 6
	Maximum Pre-Charged Piping Length	ft [m]	165 [50]
	Additional Refrigerant Charge Per Additional Piping Length	oz/ft	0
Piping	Liquid Pipe Size O.D. [Flared]	inch [mm]	1/4 [6.35]
	Gas Pipe Size O.D. [Flared]	inch [mm]	1/2 [12.7]
	Maximum Piping Length	ft [m]	165 [50]
	Maximum Height Difference	ft [m]	100 [30]

Notes

¹Cooling at 95°F (Indoor // Outdoor) °F 80 DB, 67 WB // 95 DB, 75 WB

*Indoor/Outdoor Unit Operating Temperature Range (Cooling Air Temp [Maximum / Minimum]): • Wind baffles required to operate below 23°F DB in cooling mode. • Cooling-only system with advanced wind baffle: -40°F - 115°F. • Refer to wind baffle documentation for further information.

**Outdoor Unit Operating Temperature Range (Cooling Thermal Lock-out / Re-start Temperatures):

SPECIFICATIONS: PKA-AL12NL & PUY-AK12NL

Piping	Maximum Number of Bends		15
Notes ¹Cooling at 95°F (Indoor // Outdoor) °F 80 DB, 67 WB // 95 DB, 75 WB *Indoor/Outdoor Unit Operating Temperature Range (Cooling Air Temp [Maximum / Minimum]): • Wind baffles required to operate below 23°F DB in cooling mode. • Cooling-only system with advanced wind baffle: -40°F - 115°F. • Refer to wind baffle documentation for further information. **Outdoor Unit Operating Temperature Range (Cooling Thermal Lock-out / Re-start Temperatures):			


INDOOR UNIT ACCESSORIES: PKA-AL12NL

Condensate	Blue Diamond MicroBlue Mini Condensate Pump 110208230V up to 18000 BTUH	☐ X85-003
	Refco Condensate Pump 100-240V up to 120k BTU/h	☐ COMBI
	Drain Pan Level Sensor/Control	☐ SS610E
	Blue Diamond MaxiBlue Condensate Pump with Reservoir Sensor 115-230V up to 48k BTU/h	☐ X88-721
	Refco Condensate Pump 100-240 VAC	☐ GOBI-II
	Blue Diamond MegaBlue Condensate Pump with Reservoir Sensor 115-230V up to 170k BTU/h	☐ X87-835
	Blue Diamond MaxiBlue Advanced Mini Condensate Pump w Reservoir Sensor 110V up to 48000 BTUH recommended	☐ X87-711
	REFCO PUMP 100-240 VAC 5060 HZ	☐ X86-011
	Blue Diamond Sensor Extension Cable 15 Ft	☐ C13-103
	Sauermann Condensate Pump 120-230V up to 60k BTU/h	☐ SI30-230
Control Interface	kumo station® for Comfort app	☐ PAC-WHS01HC-E
	Airzone Wireless Think Controller White	☐ AZZBSTHINKRB
	Wireless Interface 2 for Comfrot app	☐ PAC-USWHS002-WF-2
	IT Extender	☐ PAC-WHS01IE-E
	Airzone Wireless Lite Controller White	☐ AZZBSLITERB
	Procon BACnet® and Modbus® Interface	☐ PAC-UKPRC001-CN-1
	Airzone Wired Blueface Controller Black	☐ AZZBSBLUEZEROCN
	Airzone Wired Blueface Controller White	☐ AZZBSBLUEZEROCB
	Thermostat Interface for 3rd Party Thermostats	☐ PAC-US445CN-1
	Airzone Wireless Think Controller Black	☐ AZZBSTHINKRN
Disconnect Switch	30A600VUL fits 2 X 4 utility box - Black	☐ TAZ-MS303
	30A600VUL fits 2 X 4 utility box - White	☐ TAZ-MS303W
Drain Hose	Flexible Mini-Split Drain Hose	☐ DRX-16
Lineset	1/4 x 1/2 Lineset Twin-Tube Insulation - 30 feet	☐ MLS141212T-30
	1/4 x 1/2 Lineset Twin-Tube Insulation - 100 feet	☐ MLS141212T-100
	1/4 x 1/2 Lineset Twin-Tube Insulation - 15 feet	☐ MLS141212T-15
	1/4 x 1/2 Lineset Twin-Tube Insulation - 50 feet	☐ MLS141212T-50
	1/4 x 1/2 Lineset Twin-Tube Insulation - 65 feet	☐ MLS141212T-65
Mini-Split Wire	14 Gauge 4 wire Armored MiniSplit Cable50 ft roll	☐ SW144-50
	14 Gauge 4 wire Armored MiniSplit Cable250 ft roll	☐ SW144-250
Remote Sensor	Wall Mount Remote Temperature Sensor	☐ PAC-SE41TS-E
	Wireless temperature and humidity sensor for Comfort app	☐ PAC-USWHS003-TH-1
	Flush Mount Remote Temperature Sensor for SEZ SLZ SVZ and all P-Series models	☐ PAC-USSEN002-FM-1
Terminal Signal Adapter	Backup Heat Relay Kit	☐ CN24RELAY-KIT-CM3
	Connector and wire for On/Off and Error status using CN51 and CN52	☐ PAC-725AD
	Connector and wire for On/Off and Fan command using CN32	☐ PAC-715AD
Wired Remote Controller	Touch MA Remote Controller	☐ PAR-CT01MAU-SB
	Simple Direct Wired Remote Controller	☐ PAC-SDW01RC-1
	Simple MA Remote Controller	☐ PAC-YT53CRAU-J
	Deluxe Wired MA Remote Controller	☐ PAR-42MAAUB
Wireless Remote Controller	Wireless MA Handheld Remote Controller (requires PAR-FA32MA-E)	☐ PAR-FL32MA-E
	Lockdown Bracket for Wireless Handheld Remote Controllers	☐ RCMKP1CB
	Wireless Remote Controller	☐ PAR-SL101A-E
	Wireless RedLINK™ Remote Controller	☐ MHK2
Notes ¹ Requires MAC-3341F-E Interface to connect MA controller		


OUTDOOR UNIT ACCESSORIES: PUY-AK12NL

Air Outlet Guide	Air Outlet Guide	☐	PAC-SJ07SG-E
Control/Service Tool	Control/Service Tool	☐	PAC-SK52ST
	Maintenance Tool Interface	☐	PAC-USCMS-MN-1
	M- & P-Series Maintenance Tool Cable Set	☐	M21EC0397
Drain Socket	Drain Socket	☐	MAC-871DS
Hail Guards	Hail Guard	☐	HG-A5
M-NET Converter	M-Net Interface for P-Series	☐	PAC-SJ96MA-E
Mini-Split Wire	14 Gauge 4 wire Armored MiniSplit Cable50 ft roll	☐	SW144-50
	14 Gauge 4 wire Armored MiniSplit Cable250 ft roll	☐	SW144-250
	14 Gauge 4 wire MiniSplit Cable50 ft roll	☐	S144-50
	14 Gauge 4 wire MiniSplit Cable250 ft roll	☐	S144-250
Mounting Pad	Condensing Unit Mounting Pad 16 x 36 x 3	☐	ULTRILITE1
Snow/Rain Diverter	SnowRain Diverter	☐	SRD-2
Stand	Outdoor Unit 3-14 inch Mounting Base Pair - Plastic	☐	DSD-400P
	Condenser Wall Bracket - Stainless Steel Finish	☐	QSWBSS
	Outdoor Unit Stand 12 High	☐	QSMS1201M
	18 Single Fan Stand	☐	QSMS1801M
	Condenser Wall Bracket	☐	QSWB2000M-1
	24 Single Fan Stand	☐	QSMS2401M
Terminal Signal Adapter	Connector and wire for On/Off and Error status using CN51 and CN52	☐	PAC-725AD
	Connector and wire for On/Off and Fan command using CN32	☐	PAC-715AD
Wind Baffle	Rear Wind Baffle	☐	WB-RE4
	Front Wind Baffle	☐	WB-PA4
	Side Advanced Wind Baffle	☐	WB-SD4
Notes			

INDOOR UNIT DIMENSIONS: PKA-AL12NL



OUTDOOR UNIT DIMENSIONS: PUY-AK12NL



1340 Satellite Boulevard Suwanee, GA 30024
Toll Free: 800-433-4822 · mitsubishicomfort.com

METUS_2026-09_PROPIN

