

PVA-AA18NL & PUY-AK18NL
18,000 BTU/H MULTI-POSITION AIR HANDLER INDOOR UNIT
18,000 BTU/H COOLING ONLY OUTDOOR UNIT



Job Name:

System Reference:

Date:



INDOOR Unit ... PVA-AA18NL
OUTDOOR Unit ... PUY-AK18NL

INDOOR UNIT FEATURES

- Multi-Position Installation: Versatile installation options, including horizontal (left or right) and vertical (up or down) orientations, with included drain pans to facilitate easy setup for any configuration.
- Wi-Fi Optional: A Wireless Interface Adapter can be ordered as an accessory for field installation.
- Three Speed Fan: Adjust the fan between three speed settings to optimal comfort.
- Blow-through design: Unique blow-through design allows simple coil cleaning when the blower is removed.
- Auto Changeover: The unit will automatically switch between heating and cooling modes to maintain your desired temperature.

OUTDOOR UNIT FEATURES

- Inverter Driven Compressor: Inverter technology uses only the precise amount of energy needed to keep a space comfortable.
- Blue Fin Coating: Anti-corrosion coating that protects the outdoor heat exchanger against salt, sulfur, and other airborne contaminants that impact the efficiency and performance of the outdoor units.
- Seacoast Protection: An anti-corrosion treatment applied to the aluminum fins of the heat exchanger of the outdoor unit to protect against corrosion caused by salt, sulfur, and other airborne contaminants, especially in coastal and industrial areas.
- Low Ambient Cooling: Low ambient cooling down to -40°F providing 100% capacity with front, side and rear wind baffle kit
- Low Ambient Cooling: Low ambient cooling down to 0°F providing 100% capacity with front wind baffle kit

SPECIFICATIONS: PVA-AA18NL & PUY-AK18NL

Cooling at 95F ¹	Maximum Capacity	Btu/h	18300
	Rated Capacity	Btu/h	18000
	Minimum Capacity	Btu/h	4700
	Maximum Power Input	W	1570
	Rated Power Input	W	1530
	Moisture Removal	Pints/h	3.60
	Sensible Heat Factor		0.78
Efficiency	SEER2		18.60
	EER2 ¹		11.70
	ENERGY STAR® Certified		No
Electrical	Voltage, Phase, Frequency	V AC / V AC , Ø , Hz	208 / 230 , 1 , 60
	Guaranteed Voltage Range	V AC	198 - 253
	Voltage: Indoor - Outdoor, S1-S2	V AC	208/230
	Voltage: Indoor - Outdoor, S2-S3	V DC	12-24
	Short-circuit Current Rating [SCCR]	kA	5
	Recommended Fuse/Breaker Size (Outdoor)	A	20
	Recommended Wire Size [Indoor - Outdoor]	AWG	14
Indoor Unit	MCA	A	3
	Breaker Size	A	15
	Fan Motor Output	W	121
	Fan Motor Type		Direct-driven DC Brushless Motor
	Airflow Rate at Cooling, Dry	CFM	515 , 625 , 735
	Sound Pressure Level [Cooling]	dB (A)	31 , 36 , 40
	External Static Pressure	in.WG	0.30 , 0.50 , 0.80
	Drain Pipe Size O.D.	inch [mm]	3/4 [19.05]
	External Finish Color		Galvanized steel cabinet-Powder coated Slate Gray
	Unit Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	17 x 21-5/8 x 50-1/4 [432 x 548 x 1275]
	Package Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	18-1/8 x 28-11/16 x 56-15/16 [460 x 728 x 1446]
	Unit Weight	lbs [kg]	113 [51]
	Package Weight	lbs [kg]	133 [60]
IDU Operating Temp. Range	Cooling Intake Air Temp [Maximum / Minimum]	°FDB , °FWB / °FDB , °FWB	90 , 72 / 66 , 61
Outdoor Unit	MCA	A	16
	MOCP	A	27
	Fan Motor Output	W	51
	Airflow Rate Cooling	CFM	1590
	Coating on Heat Exchanger (Bluefin, Sea Coast)		Yes , Yes
	Sound Pressure Level, Cooling ¹	dB (A)	44
	Compressor Type		Twin Rotary
	Compressor Model		SRB140FQHMC-L1
	Compressor Oil [Type // Charge]	// oz	RM68EH // 16
	External Finish Color		Munsell 3Y 7.8/1.1
	Unit Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	34-19/16 x 11-13/16 x 24-13/16 [871 x 300 x 630]
	Package Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	37-1/16 x 16-3/16 x 32-1/4 [941 x 411 x 819]
	Unit Weight	lbs [kg]	99 [45]
	Package Weight	lbs [kg]	112.44 [51]
ODU Operating Temp. Range	Cooling Intake Air Temp [Maximum / Minimum*]	°FDB	115 / 23
	Cooling Thermal Lock-out / Re-start Temperatures**	°FDB	N/A / N/A
Refrigerant	Type		R454B
	Pre-Charged Refrigerant Amount	lbs , oz	4 , 6
	Maximum Pre-Charged Piping Length	ft [m]	165 [50]
	Additional Refrigerant Charge Per Additional Piping Length	oz/ft	0
Piping	Liquid Pipe Size O.D. [Flared]	inch [mm]	1/4 [6.35]
	Gas Pipe Size O.D. [Flared]	inch [mm]	1/2 [12.72]
	Maximum Piping Length	ft [m]	165 [50]

Notes

¹Cooling at 95°F (Indoor // Outdoor) °F 80 DB, 67 WB // 95 DB, 75 WB

*Indoor/Outdoor Unit Operating Temperature Range (Cooling Air Temp [Maximum / Minimum]): • Wind baffles required to operate below 23°F DB in cooling mode. • Cooling-only system with advanced wind baffle: -40°F - 115°F. • Refer to wind baffle documentation for further information.

**Outdoor Unit Operating Temperature Range (Cooling Thermal Lock-out / Re-start Temperatures):

SPECIFICATIONS: PVA-AA18NL & PUY-AK18NL

Piping	Maximum Height Difference	ft [m]	100 [30]
	Maximum Number of Bends		15

Notes

- ¹Cooling at 95°F (Indoor // Outdoor) °F 80 DB, 67 WB // 95 DB, 75 WB
*Indoor/Outdoor Unit Operating Temperature Range (Cooling Air Temp [Maximum / Minimum]); • Wind baffles required to operate below 23°F DB in cooling mode. • Cooling-only system with advanced wind baffle: -40°F - 115°F. • Refer to wind baffle documentation for further information.
**Outdoor Unit Operating Temperature Range (Cooling Thermal Lock-out / Re-start Temperatures):

INDOOR UNIT ACCESSORIES: PVA-AA18NL

Condensate	Blue Diamond MegaBlue Condensate Pump with Reservoir Sensor 115-230V up to 170k BTU/h	☐ X87-835
	Blue Diamond MaxiBlue Condensate Pump with Reservoir Sensor 115-230V up to 48k BTU/h	☐ X88-721
	Blue Diamond MaxiBlue Advanced Mini Condensate Pump w Reservoir Sensor 110V up to 48000 BTUH recommended	☐ X87-711
	Blue Diamond Sensor Extension Cable 15 Ft	☐ C13-103
	Blue Diamond MicroBlue Mini Condensate Pump 110208230V up to 18000 BTUH	☐ X86-003
	Refco Condensate Pump 100-240V up to 120k BTU/h	☐ COMBI
	Sauermann Condensate Pump 120-230V up to 60k BTU/h	☐ SI30-230
Control Interface	Procon BACnet® and Modbus® Interface	☐ PAC-UKPRC001-CN-1
	Operation and Error Status Output Adapter	☐ PAC-SF40RM-E
	IT Extender	☐ PAC-WHS01IE-E
	Airzone Wired Lite Controller White	☐ AZZBSLITECB
	Airzone Wired Blueface Controller Black	☐ AZZBSBLUEZEROCN
	Airzone Wireless Think Controller Black	☐ AZZBSTHINKRN
	Airzone Wired Blueface Controller White	☐ AZZBSBLUEZEROCB
	Wireless Interface 2 for Comfrot app	☐ PAC-USWHS002-WF-2
	kumo station® for Comfort app	☐ PAC-WHS01HC-E
	Thermostat Interface for 3rd Party Thermostats	☐ PAC-US445CN-1
	Airzone Wireless Think Controller White	☐ AZZBSTHINKRB
	Airzone Wireless Lite Controller White	☐ AZZBSLITERB
Control Wire	202PR shielded 1PR plenum wire for Airzone 500 ft reel	☐ CW2042S2-500
	202PR 1PR shielded 1PR plenum wire for Airzone 100 ft reel	☐ CW2042S2-100
Disconnect Switch	30A600VUL fits 2 X 4 utility box - Black	☐ TAZ-MS303
	30A600VUL fits 2 X 4 utility box - White	☐ TAZ-MS303W
Downflow Kit	Downflow Kit	☐ CMA-1
Electric Heat Lockout	Electric Heat Lockout	☐ ETC-211020-MIT
Electric Kit Heats	3kW Electric Heater Module - Small Cabinet	☐ EH03-MPA-SB
	8kW Electric Heater Module - Small Cabinet	☐ EH08-MPA-SB
	5kW Electric Heater Module - Small Cabinet	☐ EH05-MPA-SB
Lineset	1/4 x 1/2 Lineset Twin-Tube Insulation - 15 feet	☐ MLS141212T-15
	1/4 x 1/2 Lineset Twin-Tube Insulation - 100 feet	☐ MLS141212T-100
	1/4 x 1/2 Lineset Twin-Tube Insulation - 50 feet	☐ MLS141212T-50
	1/4 x 1/2 Lineset Twin-Tube Insulation - 30 feet	☐ MLS141212T-30
	1/4 x 1/2 Lineset Twin-Tube Insulation - 65 feet	☐ MLS141212T-65
Remote Sensor	Wall Mount Remote Temperature Sensor	☐ PAC-SE41TS-E
	Flush Mount Remote Temperature Sensor for SEZ SLZ SVZ and all P-Series models	☐ PAC-USSEN002-FM-1
	Wireless temperature and humidity sensor for Comfort app	☐ PAC-USWHS003-TH-1
Terminal Block	Separate Terminal Power Block	☐ SPTB1
Terminal Signal Adapter	ERV On/Off Input Adapter for CNER on SVZ PEAD and PVA models	☐ PAC-740
	Connector and wire for On/Off and Fan command using CN32	☐ PAC-715AD
	Connector and wire for On/Off and Error status using CN51 and CN52	☐ PAC-725AD
	Backup Heat Relay Kit	☐ CN24RELAY-KIT-CM3
Wired Remote Controller	Deluxe Wired MA Remote Controller	☐ PAR-42MAAUB
	Simple MA Remote Controller	☐ PAC-YT53CRAU-J
	Simple Direct Wired Remote Controller	☐ PAC-SDW01RC-1
	Touch MA Remote Controller	☐ PAR-CT01MAU-SB
Wireless Remote Controller	Lockdown Bracket for Wireless Handheld Remote Controllers	☐ RCMKP1CB
	Wireless Remote Controller	☐ PAR-SL101A-E
	Wireless MA Handheld Remote Controller (requires PAR-FA32MA-E)	☐ PAR-FL32MA-E
	Universal Wireless Receiver for PAR-FL32MA-E	☐ PAR-FA32MA-W
	Wireless RedLINK™ Remote Controller	☐ MHK2

Notes


¹Requires MAC-334IF-E Interface to connect MA controller

¹Unable to use with Wireless Handheld Remote Controller


OUTDOOR UNIT ACCESSORIES: PUY-AK18NL

Air Outlet Guide	Air Outlet Guide	☐	PAC-SJ07SG-E
Control/Service Tool	Control/Service Tool	☐	PAC-SK52ST
	Maintenance Tool Interface	☐	PAC-USCMS-MN-1
	M- & P-Series Maintenance Tool Cable Set	☐	M21EC0397
Drain Socket	Drain Socket	☐	MAC-871DS
Hail Guards	Hail Guard	☐	HG-A5
M-NET Converter	M-Net Interface for P-Series	☐	PAC-SJ96MA-E
Mini-Split Wire	14 Gauge 4 wire MiniSplit Cable250 ft roll	☐	S144-250
	14 Gauge 4 wire Armored MiniSplit Cable250 ft roll	☐	SW144-250
	14 Gauge 4 wire Armored MiniSplit Cable50 ft roll	☐	SW144-50
	14 Gauge 4 wire MiniSplit Cable50 ft roll	☐	S144-50
Mounting Pad	Condensing Unit Mounting Pad 16 x 36 x 3	☐	ULTRILITE1
Snow/Rain Diverter	SnowRain Diverter	☐	SRD-2
Stand	Outdoor Unit Stand 12 High	☐	QSMS1201M
	18 Single Fan Stand	☐	QSMS1801M
	Outdoor Unit 3-14 inch Mounting Base Pair - Plastic	☐	DSD-400P
	Condenser Wall Bracket	☐	QSWB2000M-1
	24 Single Fan Stand	☐	QSMS2401M
	Condenser Wall Bracket - Stainless Steel Finish	☐	QSWBSS
Terminal Signal Adapter	Connector and wire for On/Off and Fan command using CN32	☐	PAC-715AD
	Connector and wire for On/Off and Error status using CN51 and CN52	☐	PAC-725AD
Wind Baffle	Rear Wind Baffle	☐	WB-RE4
	Side Advanced Wind Baffle	☐	WB-SD4
	Front Wind Baffle	☐	WB-PA4
Notes			

INDOOR UNIT DIMENSIONS: PVA-AA18NL

[illegible]

METUS_2026-09_PROPIN



1340 Satellite Boulevard Suwanee, GA 30024
Toll Free: 800-433-4822 · mitsubishicomfort.com

