S-MEXT-G06-M1-O-18LA & PUZ-AK60NL
50,200 BTU/H STANDARD OVER FLOW IT COOLING INDOOR UNIT
60,000 BTU/H HEAT PUMP OUTDOOR UNIT

Job Name:			
System Reference:		**Date:**	

INDOOR Unit ... S-MEXT-G06-M1-O-18LA

OUTDOOR Unit ... PUZ-AK60NL

INDOOR UNIT FEATURES

- Computer Room Air Conditioning (CRAC): Unit meets and exceeds DOE CMMS import requirements.
- Low GWP: R-454B system with continuous circulation to meet code requirements.
- Touch Screen Control Interface: Factory installed 7-inch touch screen display with intuitive navigation for operating and monitoring operation and alarm status.
- Multi-Unit Networking: Enhanced network functions that offer connection of up to 10 s-MEXT units, balancing unit operating hours (lead-lag and stand-by unit activation), and centralized control.
- Flash Memory Logging: Capable of storing up to 200 recorded events in flash memory to preserve data for easy servicing and troubleshooting. Available in absence of power supply.
- Safety Devices: Built-in automatic disconnect system with inputs for fire, refrigerant leak, water leak, and airflow loss detection.

OUTDOOR UNIT FEATURES

- Inverter Driven Compressor: Inverter technology uses only the precise amount of energy needed to keep a space comfortable.
- Blue Fin Coating: Anti-corrosion coating that protects the outdoor heat exchanger against salt, sulfur, and other airborne contaminants that impact the efficiency and performance of the outdoor units.
- Seacoast Protection: An anti-corrosion treatment applied to the aluminum fins of the heat exchanger of the outdoor unit to protect against corrosion caused by salt, sulfur, and other airborne contaminants, especially in coastal and industrial areas.
- Low Ambient Cooling: Low ambient cooling down to 0°F providing 100% capacity with front wind baffle kit

© 2026 Mitsubishi Electric Trane HVAC US LLC. All rights reserved.

SPECIFICATIONS: S-MEXT-G06-M1-O-18LA & PUZ-AK60NL

Cooling Capacity	Total Cooling Capacity	Btu/h [kW]	50,200 [14.71]
	Net Cooling Capacity	Btu/h [kW]	49,100 [14.4]
	Sensible Cooling Capacity	Btu/h [kW]	48,900 [14.33]
	Net Sensible Capacity	Btu/h [kW]	48,450 [14.2]
Efficiency	Net SCOP		2.8
	Maximum Static Pressure		1.42
Electrical	Voltage, Phase, Frequency	V AC / V AC , ø , Hz	208 / 230 , 1 , 60
	Guaranteed Voltage Range	V AC	208 - 230
	Short-circuit Current Rating [SCCR]	kA	5
Indoor Unit	MCA	A	9
	MOCP	A	10
	Fan Motor Type		EC Motor
	Rated Airflow, Dry	CFM	2413
	Sound Pressure Level		56
	Sound Power Level		72
	Drain Pipe Size O.D.	inch [mm]	7/8 [22.23]
	Unit Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	39-3/8 x 19-11/16 x 78 [1000 x 500 x 1981]
	Package Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	43-5/16 x 27-3/16 x 88-5/8 [1100 x 691 x 2251]
	Unit Weight	lbs [kg]	265 [120]
	Package Weight	lbs [kg]	401 [182]
IDU Operating Temp. Range	Cooling Intake Air Temp [Maximum / Minimum]	°FDB	95
	Cooling Intake Maximum Air Temp WB	°FWB	72
	Cooling Intake Minimum Air Temp DB	°FDB	66
	Cooling Intake Minimum Air Temp WB	°FWB	57
	Heating Intake Air Temp [Maximum / Minimum]	°FDB	115
	Heating Intake Minimum Air Temp DB	°FDB	23
Outdoor Unit	MCA	A	38
	MOCP	A	67
	Fan Motor Output	W	213
	Airflow Rate Cooling	CFM	4020
	Coating on Heat Exchanger (Bluefin, Sea Coast)		Yes , Yes
	Sound Pressure Level, Cooling[1]	dB (A)	60
	Compressor Type		Twin Rotary
	Compressor Model		MRB53FEJMC-L
	Compressor Oil [Type // Charge]	// oz	RM68EH // 60
	External Finish Color		Munsell 3Y 7.8/1.1
	Base Pan Heater		Optional
	Unit Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	41-11/32 x 14 x 52-43/64 [1050 x 355 x 1388]
	Package Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	42-15/16 x 17-3/4 x 58-5/16 [1090 x 450 x 1480]
	Unit Weight	lbs [kg]	265 [120]
	Package Weight	lbs [kg]	291 [132]
ODU Operating Temp. Range	Cooling Intake Air Temp [Maximum / Minimum*]	°FDB	115 / 23
	Cooling Thermal Lock-out / Re-start Temperatures**	°FDB	N/A / N/A
Refrigerant	Type		R454B
	Pre-Charged Refrigerant Amount	lbs , oz	11 , 7
	Maximum Pre-Charged Piping Length	ft [m]	100 [30]
	Additional Refrigerant Charge Per Additional Piping Length	oz/ft	0.6
Piping	Gas Pipe Size O.D. [Flared]	inch [mm]	3/4 [19.05]
	Liquid Pipe Size O.D. [Flared]	inch [mm]	3/8 [9.52]
	Maximum Piping Length	ft [m]	245 [75]
	Maximum Height Difference	ft [m]	100 [30]
	Maximum Number of Bends		15

Notes

[1]Cooling (Indoor // Outdoor) °F 75 DB, 52 DP (Upflow), 85 DB, 52 DP (Downflow) // 95 DB, 75 WB
*Indoor/Outdoor Unit Operating Temperature Range (Cooling Air Temp [Maximum / Minimum]): • Wind baffles required to operate below 23°F DB in cooling mode. • Heat pump system with wind baffle: 0°F - 115°F. • Refer to wind baffle documentation for further information.
**Outdoor Unit Operating Temperature Range (Cooling Thermal Lock-out / Re-start Temperatures):

© 2026 Mitsubishi Electric Trane HVAC US LLC. All rights reserved.

INDOOR UNIT ACCESSORIES: S-MEXT-G06-M1-O-18LA

S-MEXT Accessories	Silenced Plenum	☐	BL79900602
	Support Frame H 255-350mm	☐	BL79901202
	Serial Card - RS485 - RS485Card - Modbus RTU	☐	T500000085
	Plenum + 3 Grilles	☐	BL79900402
	Support Frame H 400-510mm	☐	BL79901402
	T/RH Air Probe	☐	T500000091
	Support Frame H 355-450mm	☐	BL79901302
	Serial Card - Ethernet - Pcoweb - Bacnet Over Ip/Snmp/Modbus TCP-IP + SMTP Email	☐	T500000087
	Intake Free-Cooling Plenum	☐	BL79901102
	Plenum + 3 Grilles - Class A1	☐	BL79900502
	Silenced Plenum + 1 Grille	☐	BL79900702
	Supply/Return Plenum	☐	BL79900202
	Supply/Return Plenum - Class A1	☐	BL79900302
	Serial Card - RS485 - Pconet - Bacnet MS/TP	☐	T500000014
Notes			

© 2026 Mitsubishi Electric Trane HVAC US LLC. All rights reserved.

OUTDOOR UNIT ACCESSORIES: PUZ-AK60NL

Air Outlet Guide	Air Outlet Guide 1 Piece	☐ PAC-SH96SG-E (two pieces required)
Centralized Drain Pan	Centralized Drain Pan	☐ PAC-SH97DP-E
Control/Service Tool	Maintenance Tool Interface	☐ PAC-USCMS-MN-1
	M- & P-Series Maintenance Tool Cable Set	☐ M21EC0397
	ControlService Tool	☐ PAC-SK52ST
Drain Socket	Drain Socket	☐ PAC-SG61DS-E
Hail Guards	Hail Guard	☐ HG-A2
M-NET Converter	M-Net Interface for P-Series	☐ PAC-SJ95MA-E
Mini-Split Wire	14 Gauge 4 wire Armored MiniSplit Cable50 ft roll	☐ SW144-50
	14 Gauge 4 wire MiniSplit Cable250 ft roll	☐ S144-250
	14 Gauge 4 wire MiniSplit Cable50 ft roll	☐ S144-50
	14 Gauge 4 wire Armored MiniSplit Cable250 ft roll	☐ SW144-250
Mounting Pad	Condensing Unit Mounting Pad 24 x 42 x 3	☐ ULTRILITE2
Optional Defrost Heater	Optional Defrost Heater	☐ PAC-SL11BH-E
Snow/Rain Diverter	SnowRain Diverter	☐ SRD-5
Stand	Outdoor Unit 3-14 inch Mounting Base Pair - Plastic	☐ DSD-400P
	Outdoor Unit Stand 12 High	☐ QSMS1202M
	24 Dual Fan Stand	☐ QSMS2402M
	18 Dual Fan Stand	☐ QSMS1802M
Terminal Signal Adapter	Connector and wire for On/Off and Fan command using CN32	☐ PAC-715AD
	Connector and wire for On/Off and Error status using CN51 and CN52	☐ PAC-725AD
Wind Baffle	Side Advanced Wind Baffle	☐ WB-SD6
	Front Wind Baffle	☐ WB-PA3 (two pieces required)
	Rear Wind Baffle	☐ WB-RE6
Notes		

© 2026 Mitsubishi Electric Trane HVAC US LLC. All rights reserved.

INDOOR UNIT DIMENSIONS: S-MEXT-G06-M1-O-18LA



© 2026 Mitsubishi Electric Trane HVAC US LLC. All rights reserved.

OUTDOOR UNIT DIMENSIONS: PUZ-AK60NL



1340 Satellite Boulevard Suwanee, GA 30024
Toll Free: 800-433-4822 · mitsubishicomfort.com

METUS_2026-09_PROPIN

Specifications are subject to change without notice.

© 2026 Mitsubishi Electric Trane HVAC US LLC. All rights reserved.