

S-MEXT-G06-M1-U-06LB & PUZ-AH24NL
23,500 BTU/H PREMIUM UNDER FLOW IT COOLING INDOOR UNIT
23,600 BTU/H HEAT PUMP OUTDOOR UNIT



Job Name:

System Reference:

Date:



INDOOR Unit ... S-MEXT-G06-M1-U-06LB
OUTDOOR Unit ... PUZ-AH24NL

INDOOR UNIT FEATURES

- Humidity Control: Control humidification and dehumidification setpoints against ambient conditions.
- Steam Humidifier: Equipped with modulating steam humidifier for advanced humidity control.
- Electric Heater: Aluminum element electric heater installed downstream of main cooling coil.
- Computer Room Air Conditioning (CRAC): Unit meets and exceeds DOE CMMS import requirements.
- Low GWP: R-454B system with continuous circulation to meet code requirements.
- Touch Screen Control Interface: Factory installed 7-inch touch screen display with intuitive navigation for operating and monitoring operation and alarm status.
- Multi-Unit Networking: Enhanced network functions that offer connection of up to 10 s-MEXT units, balancing unit operating hours (lead-lag and stand-by unit activation), and centralized control.
- Flash Memory Logging: Capable of storing up to 200 recorded events in flash memory to preserve data for easy servicing and troubleshooting. Available in absence of power supply.
- Safety Devices: Built-in automatic disconnect system with inputs for fire, refrigerant leak, water leak, and airflow loss detection.

OUTDOOR UNIT FEATURES

- Inverter Driven Compressor: Inverter technology uses only the precise amount of energy needed to keep a space comfortable.
- Blue Fin Coating: Anti-corrosion coating that protects the outdoor heat exchanger against salt, sulfur, and other airborne contaminants that impact the efficiency and performance of the outdoor units.
- Seacoast Protection: An anti-corrosion treatment applied to the aluminum fins of the heat exchanger of the outdoor unit to protect against corrosion caused by salt, sulfur, and other airborne contaminants, especially in coastal and industrial areas.
- Low Ambient Cooling: Low ambient cooling down to 0°F providing 100% capacity with front wind baffle kit

SPECIFICATIONS: S-MEXT-G06-M1-U-06LB & PUZ-AH24NL

Cooling Capacity	Total Cooling Capacity	Btu/h [kW]	23,500 [6.88]
	Net Cooling Capacity	Btu/h [kW]	22,900 [6.71]
	Sensible Cooling Capacity	Btu/h [kW]	23,100 [6.77]
	Net Sensible Capacity	Btu/h [kW]	20,470 [6]
Efficiency	Net SCOP		2.8
	Maximum Static Pressure		1.66
Electrical	Voltage, Phase, Frequency	V AC / V AC , Ø , Hz	208 / 230 , 1 , 60
	Guaranteed Voltage Range	V AC	208 - 230
	Short-circuit Current Rating [SCCR]	kA	5
	MCA	A	30.90
Indoor Unit	MOCP	A	35
	Fan Motor Type		EC Motor
	Rated Airflow, Dry	CFM	1180
	Sound Pressure Level		55
	Sound Power Level		71
	Drain Pipe Size O.D.	inch [mm]	7/8 [22.23]
	Unit Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	23-5/8 x 19-11/16 x 78 [600 x 500 x 1981]
	Package Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	29-1/2 x 25-5/8 x 87-3/8 [749 x 651 x 2219]
	Unit Weight	lbs [kg]	154 [70]
	Package Weight	lbs [kg]	309 [140]
IDU Operating Temp. Range	Cooling Intake Air Temp [Maximum / Minimum]	°FDB	95
	Cooling Intake Maximum Air Temp WB	°FWB	72
	Cooling Intake Minimum Air Temp DB	°FDB	66
	Cooling Intake Minimum Air Temp WB	°FWB	57
	Heating Intake Air Temp [Maximum / Minimum]	°FDB	115
	Heating Intake Minimum Air Temp DB	°FDB	23
Outdoor Unit	MCA	A	22
	MOCP	A	37
	Fan Motor Output	W	74
	Airflow Rate Cooling	CFM	1940
	Coating on Heat Exchanger (Bluefin, Sea Coast)		Yes , Yes
	Sound Pressure Level, Cooling ¹	dB (A)	49
	Compressor Type		Twin Rotary
	Compressor Model		SRB172FQHMC-L1
	Compressor Oil [Type // Charge]	// oz	RM68EH // 23
	External Finish Color		Munsell No.3Y 7.8/1.1
	Base Pan Heater		Optional
	Unit Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	37-13/32 x 14 x 37-1/8 [950 x 355 x 943]
	Package Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	41-15/16 x 17-3/4 x 42-1/2 [1065 x 450 x 1079]
	Unit Weight	lbs [kg]	155 [70]
	Package Weight	lbs [kg]	179 [81]
ODU Operating Temp. Range	Cooling Intake Air Temp [Maximum / Minimum*]	°FDB	115 / 23
	Cooling Thermal Lock-out / Re-start Temperatures**	°FDB	N/A / N/A
Refrigerant	Type		R454B
	Pre-Charged Refrigerant Amount	lbs , oz	7 , 11
	Maximum Pre-Charged Piping Length	ft [m]	100 [30]
	Additional Refrigerant Charge Per Additional Piping Length	oz/ft	0.6
Piping	Gas Pipe Size O.D. [Flared]	inch [mm]	5/8 [15.88]
	Liquid Pipe Size O.D. [Flared]	inch [mm]	3/8 [9.52]
	Maximum Piping Length	ft [m]	100 [30]
	Maximum Height Difference	ft [m]	100 [30]
	Maximum Number of Bends		15

Notes

¹Cooling (Indoor // Outdoor) °F 75 DB, 52 DP (Upflow), 85 DB, 52 DP (Downflow) // 95 DB, 75 WB

*Indoor/Outdoor Unit Operating Temperature Range (Cooling Air Temp [Maximum / Minimum]): • Wind baffles required to operate below 23°F DB in cooling mode. • Heat pump system with wind baffle: 0°F - 115°F. • Refer to wind baffle documentation for further information.

**Outdoor Unit Operating Temperature Range (Cooling Thermal Lock-out / Re-start Temperatures):


INDOOR UNIT ACCESSORIES: S-MEXT-G06-M1-U-06LB

S-MEXT Accessories	Silenced Plenum	☐	BL79900601
	Serial Card - RS485 - Pconet - Bacnet MS/TP	☐	T500000014
	Supply/Return Plenum - Class A1	☐	BL79900301
	Silenced Plenum + 1 Grille	☐	BL79900701
	Plenum + 3 Grilles - Class A1	☐	BL79900501
	Support Frame H 255-350mm	☐	BL79901201
	Intake Free-Cooling Plenum	☐	BL79901101
	T/RH Air Probe	☐	T500000091
	Support Frame H 400-510mm	☐	BL79901401
	Support Frame H 355-450mm	☐	BL79901301
	Supply/Return Plenum	☐	BL79900201
	Damper With Spring Return	☐	T500000180
	Plenum + 3 Grilles	☐	BL79900401
	Serial Card - RS485 - RS485Card - Modbus RTU	☐	T500000085
	Serial Card - Ethernet - Pcoweb - Bacnet Over Ip/Snmp/Modbus TCP-IP + SMTP Email	☐	T500000087
Notes			

OUTDOOR UNIT ACCESSORIES: PUZ-AH24NL

Air Outlet Guide	Air Outlet Guide 1 Piece	☐	PAC-SG59SG-E
Centralized Drain Pan	Centralized Drain Pan	☐	PAC-SG64DP-E
Control/Service Tool	ControlService Tool	☐	PAC-SK52ST
	M- & P-Series Maintenance Tool Cable Set	☐	M21EC0397
Drain Socket	Drain Socket	☐	PAC-SG61DS-E
Hail Guards	Hail Guard	☐	HG-A6
M-NET Converter	M-Net Interface for P-Series	☐	PAC-SJ95MA-E
Mini-Split Wire	14 Gauge 4 wire Armored MiniSplit Cable250 ft roll	☐	SW144-250
	14 Gauge 4 wire Armored MiniSplit Cable50 ft roll	☐	SW144-50
	14 Gauge 4 wire MiniSplit Cable250 ft roll	☐	S144-250
	14 Gauge 4 wire MiniSplit Cable50 ft roll	☐	S144-50
Mounting Pad	Condensing Unit Mounting Pad 24 x 42 x 3	☐	ULTRILITE2
Optional Defrost Heater	Optional Defrost Heater	☐	PAC-SK62BH-E
Snow/Rain Diverter	SnowRain Diverter	☐	SRD-4
Stand	24 Single Fan Stand	☐	QSMS2401M
	Condenser Wall Bracket - Stainless Steel Finish	☐	QSWBSS
	Condenser Wall Bracket	☐	QSWB2000M-1
	18 Single Fan Stand	☐	QSMS1801M
	Outdoor Unit Stand 12 High	☐	QSMS1201M
	Outdoor Unit 3-14 inch Mounting Base Pair - Plastic	☐	DSD-400P
Terminal Signal Adapter	Connector and wire for On/Off and Fan command using CN32	☐	PAC-715AD
	Connector and wire for On/Off and Error status using CN51 and CN52	☐	PAC-725AD
Wind Baffle	Front Wind Baffle	☐	WB-PA5
	Rear Wind Baffle	☐	WB-RE5
	Side Advanced Wind Baffle	☐	WB-SD5
Notes			

INDOOR UNIT DIMENSIONS: S-MEXT-G06-M1-U-06LB



* CON SERRANDA DI NON RITORNO
ALTEZZA TOTALE = 2070

* WITH NON RETURN MOTORIZED DAMPER
TOTAL HEIGHT= 2070

METUS_2026-09_PROPIN

